

PANEL de petite taille avec ressort



Référence	Taille de coupe	Taille Luminaire	Puissance	Couleur Température	Flux Lumineux
PR3-75-3000	75 mm	85 x 13 mm	3 w	3000K	215 lm
PR3-75-4000	75 mm	85 x 13 mm	3 w	4000K	240 lm
PR4-95-3000	95 mm	105 x 13 mm	4 w	3000K	290 lm
PR4-95-4000	95 mm	105 x 13 mm	4 w	4000K	320 lm
PR6-110-3000	110 mm	120 x 13 mm	6 w	3000K	430 lm
PR6-110-4000	110 mm	120 x 13 mm	6 w	4000K	480 lm
PR12-160-3000	160 mm	170 x 13 mm	12 w	3000K	860 lm
PR12-160-4000	160 mm	170 x 13 mm	12 w	4000K	960 lm
PR15-175-3000	175 mm	190 x 13 mm	15 w	3000K	1080 lm
PR15-175-4000	175 mm	190 x 13 mm	15 w	4000K	1200 lm
PR18-210-3000	210 mm	225 x 13 mm	18 w	3000K	1295 lm
PR18-210-4000	210 mm	225 x 13 mm	18 w	4000K	1440 lm
PR24-285-3000	285 mm	295 x 13 mm	24 w	3000K	1730 lm
PR24-285-4000	285 mm	295 x 13 mm	24 w	4000K	1920 lm

Caractéristiques Luminaire									
IRC	IP	URG	Angle de Diffusion	Variable	Option	Diode	Tension Réseau	Durée de Vie	Garantie
80	21	22	120°	Oui	1-10V	Epistar	AC85 - 265V	50 000 h	3 ans

Certifications

CE - RoHS