

TLL-T5



Référence	Dimensions	Puissance	Couleur Température	Flux Lumineux
TLL11-T5-565-3000	565 x 33 x 29 mm	11 w	3000K	1190 lm
TLL11-T5-565-4000	565 x 33 x 29 mm	11 w	4000K	1320 lm
TLL17-T5-869-3000	869 x 33 x 29 mm	17 w	3000K	1840 lm
TLL17-T5-869-4000	869 x 33 x 29 mm	17 w	4000K	2040 lm
TLL20-T5-1174-3000	1174 x 33 x 29 mm	20 w	3000K	2160 lm
TLL20-T5-1174-4000	1174 x 33 x 29 mm	20 w	4000K	2400 lm
TLL24-T5-1475-3000	1475 x 33 x 29 mm	24 w	3000K	2600 lm
TLL24-T5-1475-4000	1475 x 33 x 29 mm	24 w	4000K	2880 lm

Caractéristiques Luminaire

IRC	IP	IK	RG	MacAdam	Angle de Diffusion	Variable	Diode	Tension d'alimentation	Fréquence	Température de Fonctionnement	Durée de Vie	Garantie
90	20	03	0	3	120°	non	Epistar	AC100-277V	50 / 60 Hz	de -20° à +40°	50 000 h	5 ans



Certifications

CE - RoHS - 850°C